12/03/03 14:09:51 Page 1 PAEN02BC V3.80 PATENT ADMINISTRATION SYSTEM

Application Id : 25842 / 02 Serial Number :

Relevant Act Patents Act 1990

19/03/02 Date Application Keyed

Status : >>> MIGRATED TO NEW PATENT SYSTEM 08/08/2002 <<<

Application Type Convention application

10 Filing Date Complete Filing Date 31/10/01

Country of origin UNITED STATES OF AMERICA

Number of pages

Number of CDROMS

CDROM Presence

15 Filing fee

> Earliest Priority Date 01/11/00 Australian OPI Date 15/05/02

Applicant Name James A. Vlodek

20

5

Inventor Name James A. Vlodek

Invention Title

25 Closure with selectively operable dispense feature

Closure with selectively operable dispense feature

30 **EXAMINATION DETAILS** 

> Direction Date Request Lodgement date

Request Type

Request Fee Paid

Deferment Date First Report Date Examination Section Examiner

35 Date Sent to Exam Further Report Date Search Results Requested Search Results Received

Abstract Requested Abstract Received

Re-exam request date

40 International (Type) Search Results

ACCEPTANCE DETAILS

Date Accepted Acceptance Advert Date

Date FE Printed

45 Acceptance Type

Applicant Ref Opposition Date Amend to Spec Opposition Result

Amend to Apln

Amend to Drwg

50 Final date for Acceptance

Date Sealed Sealed Advertised Date

Accept Not Sealed Advert Lapsed Advertised Date

55 Lapsed Type

Withdrawn Advertised Date

Withdrawn Type

Refused Advertised Date Ceased/Expired Advert PAEN02BE V3.41 PATENT ADMINISTRATION SYSTEM 12/03/03 14:09:52 Page 2

Application Id : 25842 / 02

Serial Number :

5 PRIORITY DETAILS

Application

Date Number Country
01/11/00 60244934 UNITED STATES OF AMERICA

PCT DETAILS

10

PCT Number PCT/US01/45618 PCT Adv. Withdrawn Date

WIPO Number WO02/36446 PCT Filing Date 31/10/01

15 Election Flag

National Phase Date Designation Advert. 11/04/02

IPC Mark Primary ? 20 B65D 025 / 08 Y

#### (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

#### (19) World Intellectual Property Organization International Bureau

# 

#### (43) International Publication Date 10 May 2002 (10.05.2002)

#### **PCT**

English

#### (10) International Publication Number WO 02/36446 A1

(51) International Patent Classification7: B65D 25/08

(21) International Application Number: PCT/US01/45618

(22) International Filing Date: 31 October 2001 (31.10.2001)

English (26) Publication Language:

(30) Priority Data: 60/244,934 1 November 2000 (01.11.2000)

(71) Applicant and

(25) Filing Language:

(72) Inventor: VLODEK, James, A. [US/US]; 10950 Linn Court, LaGrange, IL 60525 (US).

(74) Agents: SAMPLES, Kenneth, H. et al.; Fitch, Even, Tabin & Flannery, Suite 1600, 120 South LaSalle Street, Chicago, IL 60603 (US).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

#### Published:

with international search report

[Continued on next page]

(54) Title: CLOSURE WITH SELECTIVELY OPERABLE DISPENSE FEATURE



(57) Abstract: A closure (14) for a beverage receptacle (12) is provided with a selectively operable dispense feature. A plurality of hollow plungers (16) containing different additives are disposed in the closure (14) and are selectively operable to pierce a rupturable seal (36), permitting contents to be dispensed into the re-

WO 02/36446 A1



# WO 02/36446 A1



 before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

# CLOSURF WITH SELECTIVELY OPERABLE DISPENSE FEATURE

#### CROSS-REFERENCE TO RELATED APPLICATION

This application claims benefit of United States Provisional Application Number 60/244,934, filed November 1, 2000.

#### BACKGROUND OF THE INVENTION

### 1. Field of the Invention

15

25

The present invention is related to closures having selectively operable dispensing features, and in particular to such closures employed with beverage receptacles.

# 2. Description Of The Related Art

Various arrangements have been proposed for providing beverage containers with the ability to selectively add different ingredients to complete a beverage mixture. For example, United States Patent No. 4,785,931 discloses a molded plastic closure having integral stacking support ribs and rupturable mixed compartments. Despite advances, improvements in the art are continually being sought.

# SUMMARY OF THE INVENTION

It is an object of the present invention to provide a closure having selectable dispensing features.

Another object of the present invention is to provide a closure of the above type for mating engagement with a beverage-containing receptacle.

A further object of the present invention is to provide a closure of the above-described type in which various additives can be mixed, one at a time, with the contents of the beverage receptacle. 5

10

20

WO 02/36446 PCT/US01/45618

These and other objects according to principles of the present invention are provided in a dispense enclosure for a fluid receptacle comprising:

a monolithic cylindrical body;

a plurality of plungers reciprocally mounted in said body; said plungers defining a hollow cavity for retaining the fluid additive;

said plungers further defining a lower edge portion for penetrating a breakable seal on said receptacle; and

a valve member disposed in said body, configurable between an open position for dispensing fluid from said receptacle and a closed position.

#### BRIEF DESCRIPTION OF THE DRAWINGS

- FIG. 1 is a perspective view of a beverage closure and dispensing assembly attached to a receptacle;
  - FIG. 2 is a perspective view thereof with a protective cap applied;
  - FIG. 3 is a fragmentary perspective view thereof, shown in exploded form:
    - FIG. 4 is a fragmentary perspective view thereof;
  - FIG. 5 is a perspective view of the beverage closure and dispensing assembly, taken on an enlarged scale;
    - FIG. 6 is a perspective view showing the underside thereof;
- FIG. 7 is an exploded perspective view of the beverage closure and dispensing assembly and receptacle;
  - FIG. 8 is another exploded perspective view thereof;
  - FIG. 9 is a cross-sectional view taken along the ling 9-9 of FIG. 1;
  - FIG. 10 is an exploded perspective view showing the beverage closure and dispensing assembly and receptacle;
- 30 FIG. 11 is an elevational view thereof;

5

10

15

20

30

WO 02/36446 PCT/US01/45618

FIG. 12 is an elevational view of the beverage closure and dispensing assembly shown in combination with a receptacle and a protective cover;

FIG. 13 is a top plan view thereof;

FIG. 14 is cross-sectional view taken on the line 14-14 of FIG. 12;

FIG. 15 shows a portion of cross-sectional view 14, taken on an enlarged scale;

FIG. 16 is a fragmentary cross-sectional view taken along the line 16-16 of FIG. 17, showing another embodiment of a beverage closure and dispensing assembly with receptacle;

FIG. 17 is a perspective view of a receptacle shown with an alternative beverage closure and dispensing assembly according to principles of the present invention;

FIG. 18 is an exploded perspective view thereof;

FIG. 19 shows a portion of FIG. 17, taken on an enlarged scale; and FIG. 20 is a perspective view of the alternative beverage closure and dispensing assembly.

# DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring now to the drawings, a beverage closure and dispensing assembly is generally indicated at 10. The beverage dispensing assembly includes a receptacle 12 for containing a fluid beverage component and a closure 14. As will be seen herein, closure 14 has selectable dispensing capability in order to provide different batches of beverage, or different flavored beverages, when mixed with the contents of receptacle 12. Closure 14 includes a plurality of plungers 16 disposed about a central valve member 18. Valve member 18 includes a collar 20 movable in vertical directions to open and close a valve passageway 22. Preferably, closure 14 includes a threaded cap portion 26 for engagement with a threaded finish 28 of receptacle 12. A protective cap 15 is shown in FIG. 3.

10

WO 02/36446 PCT/US01/45618

As can be seen in FIG. 1, plungers 16 include an upper closed end 30 resembling a push button for manual actuation by a user, to depress the plungers in a downward direction, toward receptacle 12. Referring to FIGS. 6, 7, and 10, it will be seen that the plungers 16 define a hollow interior cavity 32 and a lower end 34 for piercing a rupturable (foil) seal 36 affixed to receptacle 12. When the plungers 16 are depressed by a user, the plunger body is translated in a vertically downward direction, with the lower edge 34 piercing rupturable seal 36.

As indicated in the figures, four plungers are provided. Preferably, each plunger contains a different flavor additive which, when mixed with the contents of receptacle 12, produces a different flavored beverage. Upon recharging the fluid content of receptacle 12 a different plunger is depressed to pierce a different portion of the rupturable seal 36 and to mix with the receptacle contents to produce a different flavored beverage. The receptacle is subsequently re-charged and different plungers are depressed until additives in the closure have all been dispensed.

FIGS. 16-20 show a receptacle 12 in combination with an alternative beverage closure and dispensing assembly generally indicated at 100. A single plunger 102 dispenses an additive into the receptacle 12. A bottom edge 108 of the plunder pierces a rupturable seal, preferably in the form of a foil 110 (see FIG. 16).

As can be seen from the above, the present invention provides an interactive package concept that allows the end user to create his or her own "mix" for drinking. The flavor cap has 1-4 chambers loaded with different colorants and/or flavors. When the foil seal is punctured via the center shaft for single additive or any of four buttons for multiple additives, ingredients are dropped into a clear/base solution, e.g., water. Reaction of the two components can be varied to include an animated use of ingredients that move, change shape and color, etc., thus giving a visual value to the process of adding two or more components just prior to drinking.

Also, the ability to add fresh or time and light sensitive ingredients cam be accomplished with the same dynamic, e.g., powdered milk, baby formula, or vitamins, minerals and nutrients, even fresh fruit flavor.

Possibilities include, but are not limited to: sports drinks, fruit juice, flavored milk, pudding, soups and candy/novelty.

Caps may also be sold separately for additional use with reusable bottles with advantages geared for travel, camping, etc.

The drawings and the foregoing descriptions are not intended to represent the only forms of the invention in regard to the details of its construction and manner of operation. Changes in form and in the proportion of parts, as well as the substitution of equivalents, are contemplated as circumstances may suggest or render expedient; and although specific terms have been employed, they are intended in a generic and descriptive sense only and not for the purposes of limitation, the scope of the invention being delineated by the following claims.

#### What is claimed is:

5

10

A dispense enclosure for a fluid receptacle comprising:
 a monolithic cylindrical body;
 a plurality of plungers reciprocally mounted in said body;


said plungers defining a hollow cavity for retaining the fluid additive:

said plungers further defining a lower edge portion for penetrating a breakable seal on said receptacle; and

a valve member disposed in said body, configurable between an open position for dispensing fluid from said receptacle and a closed position.


- 2. The enclosure of claim 1 wherein said plurality of plungers is disposed about said valve member.
- 3. The enclosure of claim 1 wherein said plungers are reciprocally movable in directions generally parallel to one another.
- 4. The enclosure of claim 1 wherein said body includes a threaded cap portion for engagement with a threaded finish of said receptacle.
- 5. The enclosure of claim 1 wherein said plungers have a generally wedge-shaped cross-section.
- 6. The enclosure of claim 1 wherein said valve member is disposed at the center of said cap, and said plungers are disposed about said valve member.

7. The enclosure of claim 1 wherein said plunders include an upper closed end for manual engagement by a user to depress said plungers toward said receptacle, penetrating said seal.




PCT/US01/45618

2/8




PCT/US01/45618

3/8




F10 11.

PCT/US01/45618




PCT/US01/45618

5/8




F14 /3




F16 14

7/8



F16 15

PCT/US01/45618 WO 02/36446



F/G 20

F16.16

# INTERNATIONAL SEARCH REPORT

International application No. PCT/US01/45618

A. CLASSIFICATION OF SUBJECT MATTER			
IPC(7) :B65D 25/08 US CL :206/219-222; 215/6,228			
According to International Patent Classification (IPC) or to both national classification and IPC			
B. FIELDS SEARCHED			
Minimum documentation searched (classification system followed by classification symbols)			
U.S. : 206/219-222; 215/6,228			
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched			
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)			
C. DOCUMENTS CONSIDERED TO BE RELEVANT			
Category*	Citation of document, with indication, where ap	propriate, of the relevant passages	Relevant to claim No.
A	US 4,785,931 A (WEIR et al) 22 Novand 3	vember 1988, see columns 2	1
A	US 4,024,952 A (LEITZ) 24 May 1977, see abstract.		1
A	US 5,788,369 A (TSENG) 04 August 1998, see abstract.		1
	·		
Further documents are listed in the continuation of Box C. See patent family annex.			
* Special categories of cited documents: "To document defining the general state of the art which is not		"In later document published after the int date and not in conflict with the appl the principle or theory underlying th	ication but cited to understand
"E" ea	document which may throw doubts on priority claim(s) or which is  cited to establish the publication date of another cited to establish the cited to establish the publication date of another cited to establish the cite		e claimed invention cannot be red to involve an inventive *tep
"O" do	ecial reason (as specified)  coment referring to an oral disclosure, use, exhibition or other cons	"Y" document of particular relevance; the considered to involve an inventive combined with one or more other sue being obvious to a person skilled in	step when the document is h documents, such combination
	'P" document published prior to the international filing date but later "&" document member of the same patent family thun the priority date claimed		
		Date of mailing of the international search report  1 1 APR 2002	
26 FEBRUARY 2002			- p j /
Commissioner of Patents and Trademarks Box PCT		Authorized officer SHIAN LUONG	hela Veney
Washington, D.C. 20231 Facsimile No. (703) 505-5250		Telephone No. (703) 308 Techno	legal Specialist logy Center 3700

THIS PAGE BLANK (USPTO)